

# Installation Guide (With Background)

**NEWTON  
MESH**



## Step One: Clean & Dry Surface

Clean the intended surface, to ensure dirt, dust and grease are thoroughly removed.




## Step Two: Tape Decal to Surface

Position the Graphic (With the backing paper still applied) to the intended position. Attach using either magnets or masking tape.



## Step Three: Adjust & Secure Decal

Adjust accordingly until the decal is in the desired position. Create a hinge point that you can lift half of the decal, while the second half remains securely in place.



## Step Four: Peel

Fold the unsecured side of the graphic over, so the print is face to face (Be Careful not to crease or damage the vinyl). Peel away the backing paper towards the hinge point. Carefully cut the backing paper using a slitter or similar tool.



## Step Five: Applying your decal

Using a vinyl application squeegee, apply the vinyl to the desired surface, starting from middle of the graphic, working outwards from edge to edge.

**NEWTON  
MESH**



## Step Seven: Imperfections

Using your finger, apply pressure onto any remaining air bubbles and watch them disappear, giving perfect results every time!

**Need a hand? Don't worry, a member of our experienced team are here to help.  
Call us on 01953 711994 or email us at [sales@newtonmesh.co.uk](mailto:sales@newtonmesh.co.uk)**

Newton Press Ltd Trading as Newton Mesh

Registered Office: Units 7-8 Cloverfield Industrial Estate, Lopham Road, East Harling, Norfolk NR16  
2LT Directors: N.P.Ward, C.M.Ward, C.A.Ward, S.L.Ward  
Co. Reg No. 03066749 | VAT Reg. No. 637 1433 47