

Installation Guide (Without Background)

**NEWTON
MESH**



Step One: Clean & Dry Surface

Clean the intended surface, to ensure dirt, dust and grease are thoroughly removed.




Step Two: Tape Decal to Surface

Position the Graphic (With the backing paper still applied) to the intended position. Attach using either magnets or masking tape.



Step Three: Adjust & Secure Decal

Adjust accordingly until the decal is in the desired position. Create a hinge point to that you can lift half of the decal, while the second half remains securely in place.



Step Four: Peel

Fold the unsecured side of the graphic over, so the print is face to face (Be Careful not to crease or damage the vinyl and application paper). Peel away the backing paper towards the hinge point. Carefully cut the backing paper using a slitter or similar tool.



Step Five: Applying your decal

Using a vinyl application squeegee, apply the vinyl with the application paper still in situ to the desired surface, starting from middle of the graphic, working outwards from edge to edge.



Step Six: Repeat

Remove the remaining fastenings before removing the last of the backing paper. Now repeat step 5.



Step Seven: Remove the Application Tape

Once the Graphic is applied, peel away the application tape from one top corner. Applying steady pressure, slowly peel the application back on itself, from top to bottom to fully reveal the decal underneath.

**NEWTON
MESH**



Step Eight: Imperfections

Using your finger, apply pressure onto any remaining air bubbles and watch them disappear, giving perfect results every time!

**Need a hand? Don't worry, a member of our experienced team are here to help.
Call us on 01953 711994 or email us at sales@newtonmesh.co.uk**

Newton Press Ltd Trading as Newton Mesh

Registered Office: Units 7-8 Cloverfield Industrial Estate, Lopham Road, East Harling, Norfolk NR16
2LT Directors: N.P.Ward, C.M.Ward, C.A.Ward, S.L.Ward
Co. Reg No. 03066749 | VAT Reg. No. 637 1433 47